

IC-F110S/F210: 25 Watt, 8 Channel Mobile Transceiver, comes in Wide/Narrow configurations including CTCSS Encode/Decode, TOT, DTMF 5 Tone ANI Encode, HM152 Hand-Mic, Mounting Bracket Kit and Hanger Kit (excluding Decode Vehicle Antenna)

IC-F110S VHF 136-174MHz, 12.5/25kHz Channel spacing

IC-F210SF2 UHF 440-490MHz, 12.5/25kHz Channel spacing

Microphones

HM152	Microphone (Non Keypad)
HM152T	DTMF microphone
HM148	Heavy duty microphone (non keypad)
SM25	Desk Microphone, Monitor Switches

Data Cables

OPC-617	External Modem Connection Cable
---------	---------------------------------

Voice Privacy Options

UT109#02	Scrambler Frequency Inversion Type
UT110#02	Scrambler Rolling Code Type
100	Option Fitting Fee

Signaling Options

UT108	DTMF Decoder Unit
-------	-------------------

Installation Options

OPC-346	DC Cable, 20A, 3m
---------	-------------------

External Speakers

SP10	Miniature External Speaker
SP22	Standard External Speaker

Programming Equipment

CS-F100S	Dealer Programming Software disc
OPC-1122	RS232 Programming Cable
OPC-1122U	USB Programming Cable

Repeater options

DRC11357	Desktop Repeater Case
OPC-617	External Modem Connection cable (For Data Interface / Repeater Operation 2 cables required)
RPT-F210	Repeater interface kit

Please note that Programming and Set up fee is \$180

Base kit options

SEC1212	DC Power Supply-for ground installation Req SEC12200
SEC12200	Base Station Cabinet

Mounting Options

MB400	DIN Size Mounting Bracket
-------	---------------------------