

**IC-F110S/F210S** 25 Watt, 8 Channel Mobile Transceiver, comes in Wide/Narrow configurations including CTCSS Encode/Decode, TOT, DTMF 5 Tone ANI Encode, HM152 Hand-Mic, Mounting Bracket Kit and Hanger Kit (excluding Decode Vehicle Antenna)

**IC-F110S** VHF 136-174MHz, 12.5/25kHz Channel spacing

**IC-F210SF2** UHF 440-490MHz, 12.5/25kHz Channel spacing

#### Microphones

HM152 Microphone (Non Keypad)

HM152T DTMF microphone

HM148 Heavy duty microphone (non keypad)

SM25 Desk Microphone, Monitor Switches

#### Data Cables

OPC-617 External Modem Connection Cable

#### Voice Privacy Options

UT109#02 Scrambler Frequency Inversion Type

UT110#02 Scrambler Rolling Code Type

100 Option Fitting Fee

#### Signaling Options

UT108 DTMF Decoder Unit

#### Installation Options

OPC-346 DC Cable, 20A, 3m

#### External Speakers

SP10 Miniature External Speaker

SP22 Standard External Speaker

#### Programming Equipment

CS-F100S Dealer Programming Software disc

OPC-1122 RS232 Programming Cable

OPC-1122U USB Programming Cable

#### Repeater options

DRC11357 Desktop Repeater Case

OPC-617 External Modem Connection cable (For Data Interface / Repeater Operation 2 cables required)

RPT-F210 Repeater interface kit

Please note that Programming and Set up fee is \$180

#### Base kit options

SEC1212 DC Power Supply-for ground installation Req SEC12200

SEC12200 Base Station Cabinet

#### Mounting Options

MB400 DIN Size Mounting Bracket