

<b>IC-F1710/2710</b>	<b>25 Watt, 256 memory channel capability including 2-tone, 5-tone, CTCSS, DTCS and DTMF encoder and decoder as standard. HM152 Hand-Mic as supplied</b>
<b>IC-F1710</b>	<b>VHF 136-174MHz, 12.5/25kHz Channel spacing</b>
<b>IC-F2710L</b>	<b>UHF 400-470MHz, 12.5/25kHz Channel spacing</b>
<b>IC-F2710H</b>	<b>UHF 450-520MHz, 12.5/25kHz Channel spacing</b>
<b>IC-F1810/F2810</b>	<b>25 Watt, 256 memory channel capability including 2-tone, 5-tone, CTCSS, DTCS and DTMF encoder and decoder as standard, HM152 Hand-Mic. With 10 Keypad &amp; SP22 speaker as supplied</b>
<b>IC-F1810</b>	<b>VHF 136-174MHz, 12.5/25kHz Channel spacing</b>
<b>IC-F2810L</b>	<b>UHF 400-470MHz, 12.5/25kHz Channel spacing</b>
<b>IC-F2810H</b>	<b>UHF 450-520MHz, 12.5/25kHz Channel spacing</b>

#### **Microphones**

HM152	Microphone (Non Keypad)
HM152T	DTMF microphone
HM148	Heavy duty microphone (non keypad)
SM25	Desk Microphone, Monitor Switches

#### **Data Cables**

OPC-617	External Modem Connection Cable
---------	---------------------------------

#### **Voice Privacy Options**

UT109#02	Scrambler Frequency Inversion Type
UT110#02	Scrambler Rolling Code Type
UT111	LTR Trunking Unit

#### **External Speakers**

SP22	External Speaker
------	------------------

#### **Programming Equipment**

CS-F1700	Dealer Programming Software
OPC-1122	RS232 programming Cable
OPC-1122U	USB Programming Cable
500	Programming Fee

#### **Separation Kits for Remote Installation**

RMK2	Separation Kit (Req OPC-607, OPC-608 or OPC-609)
OPC-607	Cable: separation (3m)
OPC-608	Cable: separation (8m)
OPC-609	Cable: separation (1.9m)