

<b>IC-F9011 S/T</b>	<b>Handheld VHF Digital P25 Trunking Radio. Supplied with belt clip, battery pack (3040mAh Li-Ion) and antenna.</b>
<b>IC-F9011S</b>	<b>Simple Version 136-174MHz</b>
IC-F9011S	12.5kHz/25kHz Analogue channel spacing, 12.5kHz Digital channel spacing
<b>IC-F9011T</b>	<b>Keypad Version 136-174MHz</b>
IC-F9011T	12.5kHz/25kHz Analogue channel spacing, 12.5kHz Digital channel spacing
<b>IC-F9023 S/T</b>	<b>Handheld UHF Digital P25 Trunking Radio. Supplied with belt clip, battery pack (3040mAh Li-Ion) and antenna.</b>
<b>IC-F9023S/T-L</b>	<b>Low Band Version - 400-470MHz</b>
IC-F9023S-L	Simple Version 12.5kHz/25kHz Analogue channel spacing, 12.5kHz Digital channel spacing
IC-F9023T-L	Keypad Version 12.5kHz/25kHz Analogue channel spacing, 12.5kHz Digital channel spacing
<b>IC-F9023S/T-H</b>	<b>High Band Version - 450-520MHz</b>
IC-F9023S-H	Simple Version 12.5kHz/25kHz Analogue channel spacing, 12.5kHz Digital channel spacing
IC-F9023T-H	Keypad Version 12.5kHz/25kHz Analogue channel spacing, 12.5kHz Digital channel spacing

### Chargers

BC119N	4 Hour charge time. Requires AD110 adaptor
AD110	Charge Adaptor. Required for BC119N and BC121N
BC121N	Multi-Charger. 4 Hour Charge Time. Requires BC157V and 6 x AD110
BC157V	AC Adaptor. Required For BC121N
OPC-515L	13.8 DC Cord for BC119N. For use with external power.
CP17L	Cigarette Lighter Cable for use with BC119N
OPC-656	12V DC Lead for BC121N

### Battery Options

BP254	Li-Ion Battery, 3040mAh. As supplied
BP237	Battery Case. Requires 6 x AA Alkaline Cells. IPX4 water protection rating
NBP254	Li-Ion Battery, 3200mAh. Suits Motorola Charger (OEM)

### Remote Audio Options

HM184	Rugged Speaker Microphone. IP57 protection rating
HS94	Earhook Headset. Requires VS-1MC
HS95	Behind the Head Headset. Requires VS-1MC
HS97	Throat Microphone. Requires VS-1MC
VS1MC	VOX PTT for HS94, HS95 and HS97
AD999	Hirose Adaptor

### Internal Units

UT124R	Man Down unit
UT125	AES/DES Encryption unit
UT128	DES Encryption unit
Belt Clip	
MB115	Alligator Type. As supplied

### Antennas

FAS25V	136-184MHz
FAS65V	148-160MHz (Same as Supplied)
FAS66V	160-174MHz
FAS67VC	Cut Antenna. 136-174MHz

### Programming Equipment

CS-F9511	Dealer Programming Software. Requires OPC-1862
----------	--

OPC-1862 Programming Cable (PC-Tr) Requires CS-F9511 Software

**Carry Case**

LC9020S Heavy Duty Leather Case with Swivel

**Zone Copy Cables**

OPC-1870 Handheld to Handheld Cable

OPC-1871 Handheld to Mobile Cable

**Keyloader Software**

OPC-1534A Keyloader Cable (OEM)